



DATA SHEET

DIFFERENTIAL PRESSURE SWITCHES SI-DPMS

The Si-DMPS mechanical differential pressure switches offer a reliable solution for a simple and yet effective pressure control of aeraulic elements, such as ducts, filters or fans.

It also suits for over heating protection and frost protection in industrial cooling systems. Easy to install, field selectable switching point.

They can be mounted in parallel with a manometer.



Cost-effective solution to monitor key air treatment and control systems in HVACR installations and building automation




Field selectable threshold for quick configuration



Convenient offer, with various differential pressure ranges



Easy to install. The mounting accessories are delivered with the instrument



Presentation of the range

Model	Setting range ¹	Switching Differential	Maximum pressure	Tolerances
Si-DPMS-1	20-200 Pa	10 Pa	10 000 Pa	≤ ±15 %
Si-DPMS-2	50-500 Pa	20 Pa		≤ ±15 %
Si-DPMS-3	200-1000 Pa	100 Pa		≤ ±15 %
Si-DPMS-4	500-2500 Pa	150 Pa		≤ ±15 %
Si-DPMS-5	1000-5000 Pa	250 Pa		≤ ±15 %

¹ Pressure values referred to vertical installation. If the device is installed horizontally, these values increase by 20 Pa.

The Si-DPMS pressure switches are supplied with protective cover, mounting bracket, mounting screws, pressure connectors and clear tube.


General features

Media	Air, non-combustible and non-aggressive gases		
Maximum pressure	10 kPa		
Mounting	Vertical		
Protection	IP54 (with cover), IP00 (without cover)		
Operating temperature	-40 °C to +85 °C		
Relay type	SPDT		
Electrical rating	Resistance: initial: $<$ 50 m Ω Current: 1.5 A (0.4 A) / 250 V		
Contact terminals	6.3 mm x 0.8 mm blade or screw terminal		
Connection	Ø 6.0 mm for tube connection		
Certification	CE		

Main Applications

- Monitoring of filter clogging in HVAC installations
- Monitoring of fans in HVAC installations
- Dynamic pressure and air flow monitoring
- Dampers and valves monitoring

Wiring





Disconnect the device from any power supply before opening the cover.

Included accessories

- 1.5 m clear PVC tube
- 2x pressure connectors



Dimensions

Dimensions in mm

